

# **Material Safety Data Sheet**

**Parsitherm 7093B** Heat Resistance Modified Acrylic Aluminum Silicone Code: **P6I04-00** Creation Date: 10,Jan.12 Page 1 of 3

1. Identification of subs	dentification of substance:		
Product name: Product usage:	Parsitherm 7093B One component aluminum heat resistance coating up to 250°C based on modified acrylic silicone.		
2. <u>Company :</u>			
Name:	Parsifam Co.		
Address:	Km 6, Noor Battery Road, Shahriar City- Iran		
Postal Code:	33561-85774		
Tel:	+98 21 6576 4960-8		
Fax:	+98 21 6576 4969		
3. Composition :			
Contains:	Modified Silicone Acrylic Resins, Aluminum Pigments, Aromatic Solvents.		
4. Hazards Identification	<u>n :</u>		
Flammable:	Avoid naked flames and hot surfaces. NO SMOKING.		
Harmful:	Possible risk of irreversible effects in contact with skin.		
5. First Aid Measures :			
Inhalation:	Do not breathe fume or vapor. Remove patient to fresh air; seek medical attention.		
Eye Contact:	Wash splashes from skin or eyes immediately. Wash eyes with copious amounts of water; if irritation persists seek medical attention.		
Skin Contact:	Wash splashes from skin or eyes immediately. Remove any contaminated clothing. If symptoms persist seek medical attention.		
Ingestion:	Do not induce vomiting; give patient plenty of water to drink and seek medical attention.		
6. Fire Fighting Measure	<u>28 :</u>		
Fire Extinguishing Media:	Use foam, dry powder, carbon dioxide. Do not use water jets.		
Special Fire Fighting Procedures:	Water can be used to cool containers. Take precautions against static discharges.		
Protective Equipment:	Wear self-contained breathing apparatus, as combustion will release harmful gases. Wear protective clothing to avoid contact with skin.		



## **Material Safety Data Sheet**

### Parsithem 7093B Heat Resistance Modified Acrylic Aluminum Silicone

Code: **P6I04-00** Creation Date: 10,Jan.12 Page 2 of 3

7.	7. <u>Accidental Release Measures :</u>	
	Personal	Avoid contact with skin or eyes; wear protective
	Precautions:	clothing and ensure adequate ventilation
	Environmental	Do not contaminate watercourses or ground. Check
	Precautions :	hollows for vapor build up.
	Methods for	Cover with sawdust or proprietary absorbent. Sweep up
	cleaning up:	and then wash area with detergent and water.
8.	Handling & Storage :	
	Safe Handling	No smoking. Ensure good ventilation. Keep away from all
	Advice	sources of ignition. Keep away from food, drink and animal feeding stuffs.
	Storage:	Store in a cool, dry place in sealed containers, away
		from all sources of heat and ignition.
9.	9. Exposure Controls / Personal Protection :	
	Respiratory	Ensure good ventilation or wear suitable solvent
	Protection:	respirator.
	Eye Protection:	Safety goggles.
	Hand Protection :	Wear (PVC/Rubber) gloves.

Skin Protection : Wear suitable protective clothing to avoid contact with skin.

### 10. Physical & Chemical Properties :

Physical State:	Base: Liquids
Color:	Silver Gray
Odor :	Aromatic Solvent.
Flash Point :	Min. 35°C
Flammability :	Flammable
V.O.C :	≈ 540 g/lit
Oxidizing Properties:	Avoid contact with strong oxidizing agents



### **Material Safety Data Sheet**

Parsithem 7093B Heat Resistance Modified Acrylic Aluminum Silicone Code: P6I04-00 Creation Date: 10,Jan.12 Page 3 of 3

Specific Gravity (at 20°C): 1.08 ± 0.05 (g/cc)

Shelf Life (at 20°C) :

12 months

### 11. Transport Information :

Dispose of according to all state and local applicable regulations.

#### 12. Regularity Information :

R10 :	FLAMMABLE
R40/41 :	HARMFUL; Possible risk if irreversible effects in contact with skin.
513 :	Keep away from food, drink and animal feeding stuffs.
S16 :	Keep away from sources of ignition; NO SMOKING
533 :	Take precautionary measures against static discharges.
S36 :	Wear suitable protective clothing.
551 :	Use only in well ventilated areas.

#### 13. Disposal Consideration :

- Kind : Hazardous waste
- Disposal : Do not dispose to drains and domestic trash bins. It can be disposed, when there is no possibility wash out and/or flow to water resources.