

# **Material Safety Data Sheet**

Parsitherm 7099

Heat Resistance Black Modified Acrylic Silicone

Code: P6I04-00

Creation Date: 10,Jan.12

Page 1 of 3

#### 1. Identification of substance:

Product name:

Parsitherm 7099

Product usage:

One component black heat resistance coating up to

250°C based on modified acrylic silicone.

2. Company:

Name:

Parsifam Co.

Address:

Km 6, Noor Battery Road, Shahriar City- Iran

Postal Code:

33561-85774

Tel:

+98 21 6576 4960-8

Fax:

+98 21 6576 4969

3. Composition:

Contains:

Modified Silicone Acrylic Resins, MIOX, Aromatic

Solvents.

4. Hazards Identification:

Flammable:

Avoid naked flames and hot surfaces. NO SMOKING.

Harmful:

Possible risk of irreversible effects in contact with skin.

5. First Aid Measures:

Inhalation:

Do not breathe fume or vapor. Remove patient to fresh

air; seek medical attention.

Eye Contact:

Wash splashes from skin or eyes immediately. Wash eyes with copious amounts of water; if irritation

persists seek medical attention.

Skin Contact:

Wash splashes from skin or eyes immediately. Remove any contaminated clothing. If symptoms persist seek

medical attention.

Ingestion:

Do not induce vomiting; give patient plenty of water to

drink and seek medical attention.

6. Fire Fighting Measures:

Fire Extinguishing Media:

Use foam, dry powder, carbon dioxide. Do not use water

jets.

Special Fire Fighting

Procedures:

Water can be used to cool containers. Take precautions

against static discharges.

Protective

Wear self-contained breathing apparatus, as combustion

Equipment:

will release harmful gases. Wear protective clothing to

avoid contact with skin.



# **Material Safety Data Sheet**

Parsitherm 7099

Heat Resistance Black Modified Acrylic Silicone

Code: P6I04-00

Creation Date: 10,Jan.12

Page 2 of 3

#### 7. Accidental Release Measures:

Personal

Avoid contact with skin or eyes; wear protective

Precautions:

clothing and ensure adequate ventilation

Environmental

Do not contaminate watercourses or ground. Check

Precautions:

hollows for vapor build up.

Methods for

Cover with sawdust or proprietary absorbent. Sweep up

cleaning up:

and then wash area with detergent and water.

8. Handling & Storage:

Safe Handling

No smoking. Ensure good ventilation. Keep away from all

Advice

sources of ignition. Keep away from food, drink and

animal feeding stuffs.

Storage:

Store in a cool, dry place in sealed containers, away

from all sources of heat and ignition.

9. Exposure Controls / Personal Protection :

Respiratory

Ensure good ventilation or wear suitable solvent

Protection: respirator.

Eye Protection:

Safety goggles.

Hand Protection:

Wear (PVC/Rubber) gloves.

**Skin Protection:** 

Wear suitable protective clothing to avoid contact with

skin.

10. Physical & Chemical Properties:

Physical State:

Base: Liquids

Color:

Silver Gray

Odor:

Aromatic Solvent.

Flash Point:

Min. 35°C

Flammability:

Flammable

**V.O.C**:

≈ 451.4 g/lit

Oxidizing

Avoid contact with strong oxidizing agents

Properties:



# **Material Safety Data Sheet**

#### Parsitherm 7099

# Heat Resistance Black Modified Acrylic Silicone

Code: P6I04-00

Creation Date: 10,Jan.12

Page 3 of 3

Specific Gravity

 $1.22 \pm 0.05 (g/cc)$ 

(at 20°C):

Shelf Life

12 months

(at 20°C) :

## 11. Transport Information:

Dispose of according to all state and local applicable regulations.

## 12. Regularity Information:

R10:

FLAMMABLE

R40/41:

HARMFUL; Possible risk if irreversible effects in

contact with skin.

**S13**:

Keep away from food, drink and animal feeding stuffs.

**S16**:

Keep away from sources of ignition; NO SMOKING

533:

Take precautionary measures against static discharges.

536:

Wear suitable protective clothing.

S51:

Use only in well ventilated areas.

### 13. Disposal Consideration:

Kind:

Hazardous waste

Disposal:

Do not dispose to drains and domestic trash bins. It can be

disposed, when there is no possibility wash out and/or flow

to water resources.