



# Material Safety Data Sheet

Code: P6I04-00  
Creation Date: Jan 10, 2012  
Page 1 of 3

## **Parsiguard 4204X2** **HI- Performance Epoxy Polyamide** **Intermediate**

### **1. Identification of substance:**

Product name: Parsiguard 4204X2  
Product usage: As an epoxy intermediate layer in multi-layer anti-corrosion paint systems for atmospheric applications at the request of ISO 12944-5, IPS, TOTAL, POGC and SPGC referenced systems.

### **2. Company :**

Name: Parsifam Co.  
Address: Km 6, Noor Battery Road, Shahriar City- Iran  
Postal Code: 33561-85774  
Tel: +98 21 6576 4960-8  
Fax: +98 21 6576 4969

### **3. Composition :**

Contains: Epoxy Resin, Xylene, Pigments, Fillers.

### **4. Hazards Identification :**

Flammable: Avoid naked flames and hot surfaces. NO SMOKING.  
Harmful: Possible risk of irreversible effects in contact with skin.

### **5. First Aid Measures :**

Inhalation: Do not breathe fume or vapor. Remove patient to fresh air; seek medical attention.  
Eye Contact: Wash splashes from skin or eyes immediately. Wash eyes with copious amounts of water; if irritation persists seek medical attention.  
Skin Contact: Wash splashes from skin or eyes immediately. Remove any contaminated clothing. If symptoms persist seek medical attention.  
Ingestion: Do not induce vomiting; give patient plenty of water to drink and seek medical attention.

### **6. Fire Fighting Measures :**

Fire Extinguishing Media: Use foam, dry powder, carbon dioxide. Do not use water jets.

Special Fire Fighting Procedures: Water can be used to cool containers. Take precautions against static discharges.

Protective Equipment: Wear self-contained breathing apparatus, as combustion will release harmful gases. Wear protective clothing to

avoid contact with skin.



## Material Safety Data Sheet

**Parsiguard 4204X2**  
**HI- Performance Epoxy Polyamide**  
**Intermediate**

Code: P6I04-00  
Creation Date: Jan 10,2012  
Page 2 of 3

### 7. Accidental Release Measures :

Personal Precautions: Avoid contact with skin or eyes; wear protective clothing and ensure adequate ventilation

Environmental Precautions : Do not contaminate watercourses or ground. Check hollows for vapor build up.

Methods for cleaning up: Cover with sawdust or proprietary absorbent. Sweep up and then wash area with detergent and water.

### 8. Handling & Storage :

Safe Handling Advice: No smoking. Ensure good ventilation. Keep away from all sources of ignition. Keep away from food, drink and animal feeding stuffs.

Storage: Store in a cool, dry place in sealed containers, away from all sources of heat and ignition.

### 9. Exposure Controls / Personal Protection :

Respiratory Protection: Ensure good ventilation or wear suitable solvent respirator.

Eye Protection: Safety goggles.

Hand Protection : Wear (PVC/Rubber) gloves.

Skin Protection : Wear suitable protective clothing to avoid contact with skin.

### 10. Physical & Chemical Properties :

Physical State: Base: Viscose Paint, Hardener: Yellow liquid with ammoniac odor.

Color: Gray

Odor : Aromatic Solvent.

Flash Point : Min. 35°C

Flammability : Flammable

V.O.C : ≈ 345 g/lit



## Material Safety Data Sheet

Code: P6I04-00  
Creation Date: Jan 10,2012  
Page 3 of 3

### **Parsiguard 4204X2** HI- Performance Epoxy Polyamide Intermediate

Specific Gravity  
(at 20°C) : 1.50 ± 0.05 (g/cc)

Shelf Life  
(at 20°C) : 12 months

#### **11. Transport Information :**

Dispose of according to all state and local applicable regulations.

#### **12. Regularity Information :**

R10 : FLAMMABLE

R40/41 : HARMFUL; Possible risk if irreversible effects in contact with skin.

S13 : Keep away from food, drink and animal feeding stuffs.

S16 : Keep away from sources of ignition; NO SMOKING

S33 : Take precautionary measures against static discharges.

S36 : Wear suitable protective clothing.

S51 : Use only in well ventilated areas.

#### **13. Disposal Consideration :**

Kind : Hazardous waste

Disposal : Do not dispose to drains and domestic trash bins. It can be disposed, when there is no possibility wash out and/or flow to water resources.