

# Material Safety Data Sheet

**Parsiglass 4517BP-1** High Solid Glass Flake Epoxy Phenolic For Tank Lining

Code: P6I04-00 Creation Date: Jan 10, 2012 Page 1 of 3

| Product name:                        | Parsiglass 4517BP-1   |
|--------------------------------------|---|
| Product usage:                       | It is one of the best choices for lining crude oil tanks, oil   |
|                                      | derivatives, process water, saline water, sea water, ballast  |
|                                      | tanks and most electrolyte and slurries in chemical tanks   |
|                                      | industries.   |
| 2. <u>Company :</u>                  |   |
| Name:                                | Parsifam Co.  |
| Address:                             | Km 6, Noor Battery Road, Shahriar City- Iran  |
| Postal Code:                         | 33561-85774   |
| Tel:                                 | +98 21 6576 4960-8  |
| Fax:                                 | +98 21 6576 4969  |
| 3. <u>Composition :</u>              |   |
| Contains:                            | Epoxy Resin, Xylene, Pigments, Glass Flakes, Fillers.   |
| 4. <u>Hazards Identificat</u>        | <u>ion :</u>  |
| Flammable:                           | Avoid naked flames and hot surfaces. NO SMOKING.  |
| Harmful:                             | Possible risk of irreversible effects in contact with skin.   |
| 5. First Aid Measures                | <u>.</u>  |
| Inhalation:                          | Do not breathe fume or vapor. Remove patient to fresh<br>air; seek medical attention.   |
| Eye Contact:                         | Wash splashes from skin or eyes immediately. Wash<br>eyes with copious amounts of water; if irritation<br>persists seek medical attention.    |
| Skin Contact:                        | Wash splashes from skin or eyes immediately. Remove<br>any contaminated clothing. If symptoms persist seek<br>medical attention.              |
| Ingestion:                           | Do not induce vomiting; give patient plenty of water to drink and seek medical attention.   |
| 6. Fire Fighting Measu               | ures :  |
| ire Extinguishing Medi               | a: Use foam, dry powder, carbon dioxide. Do not use water jets.   |
| Special Fire Fighting<br>Procedures: | Water can be used to cool containers. Take precautions against static discharges.   |
| Protective<br>Equipment:             | Wear self-contained breathing apparatus, as combustion<br>will release harmful gases. Wear protective clothing to<br>avoid contact with skin. |



## **Material Safety Data Sheet**

**Parsiglass 4517BP-1** High Solid Glass Flake Epoxy Phenolic For Tank Lining

Code: P6I04-00 Creation Date: Jan 10, 2012 Page 2 of 3

| 7. <u>Accidental Release Measures :</u> |  |  |
|---|--|--|
| Personal<br>Precautions:                | Avoid contact with skin or eyes; wear protective<br>clothing and ensure adequate ventilation   |  |
| Environmental<br>Precautions :          | Do not contaminate watercourses or ground. Check hollows for vapor build up.   |  |
| Methods for<br>cleaning up:             | Cover with sawdust or proprietary absorbent. Sweep up and then wash area with detergent and water.                                       |  |
| 8. Handling & Storage :                 |  |  |
| Safe Handling<br>Advice                 | No smoking. Ensure good ventilation. Keep away from all<br>sources of ignition. Keep away from food, drink and<br>animal feeding stuffs. |  |
| Storage:                                | Store in a cool, dry place in sealed containers, away from all sources of heat and ignition.   |  |
| 9. Exposure Controls / Po               | ersonal Protection :   |  |
| Despiratory                             | Ensure and ventilation or wear suitable solvent  |  |

| Respiratory<br>Protection: | Ensure good ventilation or wear suitable solvent<br>respirator. |
|----------------------------|---|
| Eye Protection:            | Safety goggles.   |
| Hand Protection :          | Wear (PVC/Rubber) gloves.                                       |
| Skin Protection :          | Wear suitable protective clothing to avoid contact with         |

### 10. Physical & Chemical Properties :

skin.

| Physical State:          | Base: Viscose Paint, Hardener: Yellow liquid with<br>ammoniac odor. |
|--------------------------|---|
| Color:                   | Off White, Gray ( becomes yellow)                                   |
| Odor :                   | Aromatic Solvent.   |
| Flash Point :            | 110 °C  |
| Flammability :           | Flammable   |
| V.O.C :                  | ≈70 gr/lit  |
| Oxidizing<br>Properties: | Avoid contact with strong oxidizing agents                          |



### **Material Safety Data Sheet**

**Parsiglass 4517BP-1** High Solid Glass Flake Epoxy Phenolic For Tank Lining Code: P6I04-00 Creation Date: Jan 10, 2012 Page 3 of 3

Specific Gravity (at 20°C): 1.4 ± 0.05 (g/cc)

Shelf Life (at 20°C):

6 months

### 11. Transport Information :

Dispose of according to all state and local applicable regulations.

### 12. Regularity Information :

| R10 :    | FLAMMABLE  |
|----------|--|
| R40/41 : | HARMFUL; Possible risk if irreversible effects in contact with skin. |
| 513 :    | Keep away from food, drink and animal feeding stuffs.                |
| S16 :    | Keep away from sources of ignition; NO SMOKING                       |
| 533 :    | Take precautionary measures against static discharges.               |
| 536 :    | Wear suitable protective clothing.                                   |
| 551 :    | Use only in well ventilated areas.                                   |

#### 13. Disposal Consideration :

- Kind : Hazardous waste
- Disposal : Do not dispose to drains and domestic trash bins. It can be disposed, when there is no possibility wash out and/or flow to water resources.