



# Material Safety Data Sheet

Code: P6I04-00  
Creation Date: Jan 10, 2012  
Page 1 of 3

## **Parsiglass 4517B-1** High Solid Glass Flake Epoxy

### **1. Identification of substance:**

Product name: Parsiglass 4517B-1  
Product usage: Anticorrosive thick coat for crude oil & light and heavy oil derivatives storage tanks and ideal lining for process water and brine tanks.

### **2. Company :**

Name: Parsifam Co.  
Address: Km 6, Noor Battery Road, Shahriar City- Iran  
Postal Code: 33561-85774  
Tel: +98 21 6576 4960-8  
Fax: +98 21 6576 4969

### **3. Composition :**

Contains: Epoxy Resin, Xylene, Pigments, Glass Flakes, Fillers.

### **4. Hazards Identification :**

Flammable: Avoid naked flames and hot surfaces. NO SMOKING.  
Harmful: Possible risk of irreversible effects in contact with skin.

### **5. First Aid Measures :**

Inhalation: Do not breathe fume or vapor. Remove patient to fresh air; seek medical attention.  
Eye Contact: Wash splashes from skin or eyes immediately. Wash eyes with copious amounts of water; if irritation persists seek medical attention.  
Skin Contact: Wash splashes from skin or eyes immediately. Remove any contaminated clothing. If symptoms persist seek medical attention.  
Ingestion: Do not induce vomiting; give patient plenty of water to drink and seek medical attention.

### **6. Fire Fighting Measures :**

Fire Extinguishing Media: Use foam, dry powder, carbon dioxide. Do not use water jets.  
Special Fire Fighting Procedures: Water can be used to cool containers. Take precautions against static discharges.  
Protective Equipment: Wear self-contained breathing apparatus, as combustion will release harmful gases. Wear protective clothing to avoid contact with skin.



## Material Safety Data Sheet

Code: P6I04-00  
Creation Date: Jan 10, 2012  
Page 2 of 3

### **Parsiglass 4517B-1** High Solid Glass Flake Epoxy

#### **7. Accidental Release Measures :**

Personal Precautions:	Avoid contact with skin or eyes; wear protective clothing and ensure adequate ventilation
Environmental Precautions :	Do not contaminate watercourses or ground. Check hollows for vapor build up.
Methods for cleaning up:	Cover with sawdust or proprietary absorbent. Sweep up and then wash area with detergent and water.

#### **8. Handling & Storage :**

Safe Handling Advice	No smoking. Ensure good ventilation. Keep away from all sources of ignition. Keep away from food, drink and animal feeding stuffs.
Storage:	Store in a cool, dry place in sealed containers, away from all sources of heat and ignition.

#### **9. Exposure Controls / Personal Protection :**

Respiratory Protection:	Ensure good ventilation or wear suitable solvent respirator.
Eye Protection:	Safety goggles.
Hand Protection :	Wear (PVC/Rubber) gloves.
Skin Protection :	Wear suitable protective clothing to avoid contact with skin.

#### **10. Physical & Chemical Properties :**

Physical State:	Base: Viscose Paint, Hardener: Yellow liquid with ammoniac odor.
Color:	Off White, Gray ( becomes yellow)
Odor :	Aromatic Solvent.
Flash Point :	110 °C
Flammability :	Flammable
V.O.C :	70 g/lit
Oxidizing Properties:	Avoid contact with strong oxidizing agents



## Material Safety Data Sheet

Code: P6I04-00  
Creation Date: Jan 10, 2012  
Page 3 of 3

### **Parsiglass 4517B-1** High Solid Glass Flake Epoxy

Specific Gravity  
(at 20°C) : 1.4 ± 0.05 (g/cc)

Shelf Life  
(at 20°C) : 6 months

#### **11. Transport Information :**

Dispose of according to all state and local applicable regulations.

#### **12. Regularity Information :**

R10 : FLAMMABLE

R40/41 : HARMFUL; Possible risk if irreversible effects in contact with skin.

S13 : Keep away from food, drink and animal feeding stuffs.

S16 : Keep away from sources of ignition; NO SMOKING

S33 : Take precautionary measures against static discharges.

S36 : Wear suitable protective clothing.

S51 : Use only in well ventilated areas.

#### **13. Disposal Consideration :**

Kind : Hazardous waste

Disposal : Do not dispose to drains and domestic trash bins. It can be disposed, when there is no possibility wash out and/or flow to water resources.